



Verti-Drain® 2519

Specifications

Sku	: 111.251.904
Working width m	: 1.95 m
Working width inch	: 76.7 inch
Max working depth mm	: 250 mm
Max working depth inch	: 10 inch
Working speed at hole spacing 65 mm kmh	: 1.75 km/h
Working speed at hole spacing 2-12 mph	: 1.08 mph
Weight kg	: 850 kg
Weight lbs	: 1874 lbs
Max diameter-solid tine mm	: 18 x 250 mm
Max diameter-solid tine inches	: 3/4 x 10 inch
Max diameter hollow tine mm	: 25 x 250 mm
Max diameter hollow tine inches	: 1 x 10 inch
Min tractor hp required	: 60 HP
Min lifting capacity kg	: 850 kg
Min lifting capacity lbs	: 1874 LBS
Max capacity with spacing 65 mm m2hr	: 3443 m ² /hr
Max capacity with spacing 2-12 ft2hr	: 37055 ft ² /hr
Three-pointhitch	: 3-Point CAT 1/2
Rpm max	: 540 rpm
Gear case oil	: 80W90 - 1.2
Dimensions mm	: 1240 x 2376 x 955 mm
Dimensions inch	: 49 x 93.5 x 37.6 inch
Slip clutch setting	: 800 Nm

Components

Solid tines 18 x 250 mm (1/2 x 10)
PTO
Toolbox with combi tool and manual

Parts