



Verti-Drain® 7215

Specifications

Sku	: 7215
Working width m	: 1.56 m
Working width inch	: 61 inch
Max working depth mm	: 250 mm
Max working depth inch	: 10 inch
Working speed at hole spacing 65 mm kmh	: 1.00 km/h
Working speed at hole spacing 2-12 mph	: 0.6 mph
Weight kg	: 550 kg
Weight lbs	: 1210 lbs
Hole distance with 12 mm tines mm	: 65 mm
Hole distance with 12 x 6 tines inches	: 2.5 inch
Hole distance with 18 mm tines mm	: 100 mm
Hole distance with 34 x 9 tines inches	: 4 inch
Hole spacing driving distance direction mm	: 25 - 165 mm
Hole spacing distance driving direction inches	: 1 - 6-1/2 inch
Max diameter-solid tine mm	: 18 x 250 mm
Max diameter-solid tine inches	: 3/4 x 10 inch
Max diameter hollow tine mm	: 25 x 250 mm
Max diameter hollow tine inches	: 1 x 10 inch
Min tractor hp required	: 25 HP
Min lifting capacity kg	: 700 kg
Min lifting capacity lbs	: 1540 LBS
Max capacity with spacing 65 mm m2hr	: 1560 m ² /hr
Max capacity with spacing 2-12 ft2hr	: 11000 ft ² /hr
Three-pointhitch	: 3-point CAT 1
Rpm max	: 500 rpm
Gear case oil	: 80W90
Lubricant	: EP 2
Dimensions mm	: 1720 x 800 x 100 mm
Dimensions inch	: 68 x 32 x 4 inch

Components

Solid tines 12 x 250 mm (1/2 x 10")
 3-speed gearbox
 Front and rear roller
 Toolbox with combi tool and manual

Parts

Hollow tines