



## Easy-Spread 1500

### Specifications

Sku	: 131.150.000
Operation	: Pulled. on tyres
Working width m	: 1.5 m
Working width inch	: 59 inch
Hopper capacity	: 0.87 m <sup>3</sup>
Hopper capacity ft <sup>3</sup>	: 30.7 FT <sup>3</sup>
Max working speed kmh	: 12 km/h
Max working speed mh	: 7.5 m/h
Weight kg	: 590 kg
Weight lbs	: 1300 lbs
Spreading thickness mm	: 0-20 mm
Spreading thickness inch	: 0 - 0.79 inch
Min tractor hp required	: 45 HP
Min lifting capacity kg	: 1300 kg
Min lifting capacity lbs	: 2866 LBS
Min oil supply of tractor lmin	: 12 l/min
Min oil supply of tractor us galmin	: 3.1 US Gal/min
Min pressure	: 70 bar
Min pressure psi	: 1015.26 bar
Required connections	: 2x Double-acting Hydraulic valve
Three-point hitch	: 3-point CAT 1-2
Dimensions mm	: 1230 x 1680 x 1740 mm
Dimensions inch	: 48.4 x 66.1 x 68.5 inch

### Components

Tipping Bucket  
 Powered gritting cylinder  
 Agitator  
 Continuously adjustable dose lid  
 Integrated adjustable legs  
 Toolbox with combi tool and manual

### Parts