



## Verti-Drain® 7516

### Specifications

Sku	:7516
Working width m	:1.6 m
Working width inch	:63 inch
Max working depth mm	:400 mm
Max working depth inch	:16 inch
Working speed at hole spacing 65 mm kmh	:0.7 km/h
Working speed at hole spacing 2-12 mph	:0.45 mph
Weight kg	:1130 kg
Weight lbs	:2490 lbs
Hole distance with 12 mm tines mm	:65 mm
Hole distance with 12 x 6 tines inches	:2.5 inch
Hole distance with 24 mm tines mm	:129 mm
Hole distance with 1 x 16 tines inches	:5 inch
Hole spacing driving distance direction mm	:50-195 mm
Hole spacing distance driving direction inches	:2 - 7-1/2 inch
Max diameter-solid tine mm	:24 x 400 mm
Max diameter-solid tine inches	:1 x 16 inch
Max diameter hollow tine mm	:32 x 300 mm
Max diameter hollow tine inches	:1-1/4 x 12 inch
Min tractor hp required	:45 HP
Min lifting capacity kg	:1350 kg
Min lifting capacity lbs	:3000 LBS
Max capacity with spacing 65 mm m2hr	:1120 m <sup>2</sup> /hr
Max capacity with spacing 2-12 ft2hr	:10200 ft <sup>2</sup> /hr
Three-pointhitch	:3-point CAT 1-2
Rpm max	:500 rpm
Gear case oil	:80W90 - 5.8
Lubricant	:EP 2
Dimensions mm	:1780 x 1000 x 1500 mm
Dimensions inch	:71 x 40 x 60 inch

### Components

Solid tines 18 x 300 mm (3/4 x 12") with adapters  
 3-speed gearbox  
 Front and rear roller  
 Toolbox with combi tool and manual

### Parts

Hollow tines